

nag_erf (s15aec)**1. Purpose**

nag_erf (s15aec) returns the value of the error function, $\operatorname{erf} x$.

2. Specification

```
#include <nag.h>
#include <nags.h>
```

```
double nag_erf(double x)
```

3. Description

The function evaluates

$$\operatorname{erf} x = \frac{2}{\sqrt{\pi}} \int_0^x e^{-t^2} dt.$$

The approximation is based on Chebyshev expansions.

4. Parameters

x

Input: the argument x of the function.

5. Error Indications and Warnings

None.

6. Further Comments**6.1. Accuracy**

On a machine with approximately 11 significant figures the function agrees with available tables to 10 figures and consistency checking with **nag_erfc (s15adc)** of the relation $\operatorname{erf} x + \operatorname{erfc} x = 1.0$ shows errors in at worst the 11th figure.

6.2. References

Abramowitz M and Stegun I A (1968) *Handbook of Mathematical Functions* Dover Publications, New York ch 7.1 p 297.

7. See Also

nag_erfc (s15adc)

8. Example

The following program reads values of the argument x from a file, evaluates the function at each value of x and prints the results.

8.1. Program Text

```
/* nag_erf(s15aec) Example Program
 *
 * Copyright 1990 Numerical Algorithms Group.
 *
 * Mark 1, 1990.
 */

#include <nag.h>
#include <stdio.h>
```

```
#include <nag_stdlib.h>
#include <nags.h>

main()
{
    double x, y;

    /* Skip heading in data file */
    Vscanf("%*[^\\n]");
    Vprintf("s15aec Example Program Results\\n");
    Vprintf("      x      y\\n");
    while (scanf("%lf", &x) != EOF)
    {
        y = s15aec(x);
        Vprintf("%12.3e%12.3e\\n", x, y);
    }
    exit(EXIT_SUCCESS);
}
```

8.2. Program Data

```
s15aec Example Program Data
      -6.0
      -4.5
      -1.0
       1.0
       4.5
       6.0
```

8.3. Program Results

```
s15aec Example Program Results
      x      y
-6.000e+00 -1.000e+00
-4.500e+00 -1.000e+00
-1.000e+00 -8.427e-01
 1.000e+00  8.427e-01
 4.500e+00  1.000e+00
 6.000e+00  1.000e+00
```
