

Item	Acceptance	Background	Fit model	Resonance parameters	Total
Fit fractions (%)					
$\rho(770)$	± 0.9	+2.0 -3.1	+0.6 -3.2	± 1.6	+2.8 -4.8
$\omega(782)$	± 0.08	+0.23 -0.06	+0.11 -0.10	+0.028 -0.014	+0.27 -0.14
$f_0(980)$	± 0.03	+0.24 -0.17	+0.21 -0.18	+0.29 -0.24	+0.43 -0.35
$f_2(1270)$	± 0.06	+0.45 -0.59	+0.85 -0.76	± 0.36	± 1.0
$\rho(1450)$	± 0.10	+0.5 -0.6	+5.6 -0.7	+0.4 -0.3	+5.6 -0.9
$f_0(500)$	± 0.4	+1.6 -0.9	+5.7 -1.6	± 0.6	+6.0 -2.0
$\lambda = 0$ fractions (%)					
$\rho(770)$	± 1.0	+1.7 -2.0	+4.9 -1.5	± 2.1	+5.7 -3.4
$\omega(782)$	± 1.5	+3.5 -1.8	+2.8 -3.5	+1.2 -1.7	+4.9 -4.5
$f_2(1270)$	± 0.3	± 2.4	+3.7 -3.4	± 1.5	± 4.5
$\rho(1450)$	± 0.9	+4.8 -8.4	+5.5 -5.1	+4.2 -6.1	+8.4 -11.6
Ratio of fit fractions (%)					
$\omega(782)/\rho(770)$	± 0.13	+0.41 -0.11	+0.18 -0.16	+0.034 -0.022	+0.47 -0.23
$f_0(980)/f_0(500)$	± 0.3	+1.5 -1.1	+1.0 -2.1	+2.2 -1.8	± 3.0