

Source	$C_{\pi\pi}$	$S_{\pi\pi}$	$A_{CP}^{B^0}$	$A_{CP}^{B_s^0}$	C_{KK}	S_{KK}	$\mathcal{A}_{KK}^{\Delta\Gamma}$
Time acceptance							
Model	0.005	0.003	0.0005	0.001	0.003	0.003	0.045
Calibration channel	0.003	0.001	0.0003	0.006	0.001	0.001	0.047
Ratios between modes	0.004	0.002	0.0010	0.000	0.001	0.001	0.047
Time resolution							
Width	0.002	0.003	0.0001	0.000	0.0009	0.010	0.000
Bias	0.000	0.000	0.0000	0.000	0.004	0.003	0.000
Average	0.000	0.001	0.0000	0.000	0.004	0.004	0.004
Input parameters	0.003	0.002	0.0001	0.000	0.006	0.007	0.047
B_s^0 from B_c^+	—	—	—	—	0.004	0.003	0.004
Flavour tagging							
Calibration model	0.001	0.001	0.0000	0.000	0.004	0.003	0.001
SSK calibration	—	—	—	—	0.003	0.004	0.000
PDF modeling							
Signal mass	0.007	0.008	0.0004	0.007	0.002	0.002	0.006
Cross-feed bkg.	0.008	0.004	0.0001	0.000	0.001	0.000	0.002
Combinatorial bkg	0.006	0.003	0.0001	0.002	0.001	0.001	0.006
3-body bkg.	0.004	0.006	0.0005	0.004	0.001	0.001	0.011
PID in fit model	0.002	0.003	0.0002	0.002	0.000	0.001	0.001
PID asymmetry	—	—	0.0028	0.003	—	—	—
Det. asymmetry	—	—	0.0012	0.001	—	—	—
Total (simultaneous)	0.015	0.013	0.0033	0.011	0.014	0.015	0.094
Total (per-candidate)	0.018	0.016	—	—	0.021	0.012	0.067