

m (GeV)	Eff. (%)	Det. resol. (%)	Bkgr. est. (%)	FSR (%)	Total (%)	Acceptance+PDF (%)
15–20	8.9	0.73	0.98	3.5	9.7	5.7
20–25	9.0	1.0	1.5	3.1	9.7	4.7
25–30	8.9	1.3	2.0	3.1	9.7	9.5
30–35	9.6	1.5	2.5	3.4	11	16
35–40	10	1.7	3.3	3.9	12	16
40–45	11	2.0	4.2	4.2	13	14
45–50	11	2.2	4.7	4.0	13	12
50–55	11	2.3	4.6	3.5	13	9.4
55–60	9.7	2.5	4.2	2.4	11	7.6
60–64	8.7	2.8	3.7	1.1	9.9	6.7
64–68	7.4	3.0	2.8	0.71	8.5	5.6
68–72	7.0	2.9	2.0	0.87	7.9	4.7
72–76	6.4	2.4	1.4	0.96	7.1	4.0
76–81	6.3	1.7	0.77	1.0	6.7	3.4
81–86	6.2	0.97	0.30	1.0	6.4	2.8
86–91	5.7	0.53	0.075	1.3	5.9	2.3
91–96	5.5	0.55	0.060	1.9	5.8	1.9
96–101	5.3	0.88	0.20	2.1	5.8	1.6
101–106	5.2	1.6	0.47	2.1	5.9	1.4
106–110	5.1	2.8	0.81	2.1	6.2	1.2
110–115	5.1	3.6	1.1	2.2	6.7	1.1
115–120	5.1	3.6	1.4	2.4	6.8	1.1
120–126	5.1	3.1	1.7	2.9	6.9	1.1
126–133	5.3	2.9	2.1	4.6	7.9	1.1
133–141	5.1	3.0	2.7	6.3	9.1	1.2
141–150	5.4	3.2	3.1	7.0	9.8	1.2
150–160	5.4	3.4	3.5	7.0	10	1.1
160–171	5.4	3.4	4.2	7.1	10	1.0
171–185	5.5	3.2	4.9	7.1	11	0.88
185–200	5.3	2.5	5.8	7.1	11	0.84
200–220	5.4	1.6	6.3	7.1	11	0.89
220–243	5.5	0.96	6.9	7.2	11	0.73
243–273	5.6	0.81	7.5	6.9	12	0.67
273–320	5.6	0.84	7.9	6.4	12	0.64
320–380	5.7	0.85	8.1	6.3	12	0.56
380–440	5.6	0.88	9.0	6.6	12	0.48
440–510	5.7	0.92	10	6.7	14	0.41
510–600	5.6	0.93	11	8.0	15	0.37
600–700	5.6	0.95	13	11	18	0.32
700–830	5.5	1.0	19	14	24	0.28
830–1000	5.5	0.96	43	14	45	0.25
1000–1500	5.3	0.82	81	13	83	0.36
1500–3000	5.2	0.76	100	12	100	0.66