

N_j	t_{mod}	$M_{\ell b}$ [GeV]	t cat.	p_T^{miss} [GeV]	Selection	$m_{\tilde{t}}$	$m_{\tilde{\chi}_1^0}$	$m_{\tilde{t}}$	$m_{\tilde{\chi}_1^0}$	$m_{\tilde{t}}$	$m_{\tilde{\chi}_1^0}$	
						[GeV]	[GeV]	[GeV]	[GeV]	[GeV]	[GeV]	
2–3	>10	≤ 175	–	600–750	0.91 ± 0.06	9.3 ± 0.7	1.1 ± 0.4	>750	2.18 ± 0.1	5.2 ± 0.5	0.26 ± 0.15	
				350–450	0.29 ± 0.03	7.7 ± 0.6	13.9 ± 1.3		U	450–600	0.6 ± 0.05	
			M	450–600	0.24 ± 0.03	5.1 ± 0.5	1.7 ± 0.4	250–450		250–450	0.13 ± 0.02	
				250–450	0.47 ± 0.04	6.1 ± 0.6	0.57 ± 0.26	450–700		450–700	0.47 ± 0.04	
	>10	>175		>700	0.75 ± 0.06	2.53 ± 0.35	0.12 ± 0.12	350–450		350–450	0.57 ± 0.05	
				450–550	0.51 ± 0.04	7.0 ± 0.5	19.4 ± 1.4	450–550		450–550	0.51 ± 0.04	
				>800	0.31 ± 0.03	4.7 ± 0.5	8.6 ± 0.9	550–650		550–650	0.31 ± 0.03	
				650–800	0.34 ± 0.04	2.29 ± 0.3	5.3 ± 0.7	>800		650–800	0.34 ± 0.04	
>4	≤ 0	≤ 175	–	250–350	0.14 ± 0.02	4.1 ± 0.4	2.5 ± 0.5	250–350	U	250–350	0.14 ± 0.02	
				350–450	0.17 ± 0.02	2.67 ± 0.34	7.7 ± 0.9	350–450		350–450	0.17 ± 0.02	
			M	450–600	0.25 ± 0.03	2.36 ± 0.31	3.9 ± 0.6	450–600	–	450–600	0.25 ± 0.03	
				>600	0.41 ± 0.05	2.13 ± 0.29	2.3 ± 0.5	450–600		450–600	0.41 ± 0.05	
	≥ 4	≥ 0		>600	0.55 ± 0.05	9.9 ± 0.7	11.3 ± 1.1	250–350	–	250–350	0.55 ± 0.05	
				250–350	0.66 ± 0.05	4.4 ± 0.4	2.9 ± 0.5	350–450		250–350	0.66 ± 0.05	
		R	350–450	0.23 ± 0.03	5.5 ± 0.5	57.2 ± 2.5	350–450	U	350–450	0.23 ± 0.03		
			250–350	0.28 ± 0.03	7.2 ± 0.6	21.1 ± 1.5	350–450		350–450	0.28 ± 0.03		
>4	0–10	≤ 175	–	250–350	0.1 ± 0.02	1.87 ± 0.29	4.1 ± 0.6	250–350	M	250–350	0.1 ± 0.02	
				350–450	0.11 ± 0.02	2.8 ± 0.4	3.4 ± 0.6	350–450		350–450	0.11 ± 0.02	
			R	250–350	0.06 ± 0.01	2.48 ± 0.33	22.0 ± 1.5	250–350	–	250–350	0.06 ± 0.01	
				350–450	0.06 ± 0.01	2.33 ± 0.33	7.7 ± 0.9	350–450		350–450	0.06 ± 0.01	
	>4	>175	–	250–350	0.05 ± 0.01	1.64 ± 0.26	5.4 ± 0.8	250–350	U	250–350	0.05 ± 0.01	
				350–450	0.08 ± 0.02	1.54 ± 0.28	3.3 ± 0.7	350–450		350–450	0.08 ± 0.02	
			R	>450	0.33 ± 0.03	3.9 ± 0.4	1.5 ± 0.4	450–550	–	450–550	0.33 ± 0.03	
				450–550	1.13 ± 0.07	21.5 ± 1.0	10.9 ± 1.0	>450		450–550	0.33 ± 0.03	
>4	>10	≤ 175	–	550–750	2.79 ± 0.1	28.1 ± 1.1	5.4 ± 0.7	550–750	U	550–750	2.79 ± 0.1	
				>750	3.43 ± 0.12	9.2 ± 0.6	1.5 ± 0.4	>750		>750	3.43 ± 0.12	
			M	250–350	0.18 ± 0.03	4.0 ± 0.4	21.8 ± 1.5	250–350	–	250–350	0.18 ± 0.03	
				350–450	0.32 ± 0.03	8.4 ± 0.6	18.4 ± 1.4	350–450		350–450	0.32 ± 0.03	
	>4	>175	–	250–350	0.05 ± 0.01	1.2 ± 0.23	1.9 ± 0.4	250–350	U	250–350	0.05 ± 0.01	
				350–450	0.23 ± 0.03	3.5 ± 0.4	3.3 ± 0.6	350–450		350–450	0.23 ± 0.03	
			R	250–350	0.04 ± 0.01	1.64 ± 0.28	7.6 ± 0.9	250–350	–	250–350	0.04 ± 0.01	
				350–450	0.11 ± 0.02	3.6 ± 0.4	6.3 ± 0.8	350–450		350–450	0.11 ± 0.02	
>4	>10	>175	–	250–500	0.17 ± 0.02	3.1 ± 0.4	4.8 ± 0.7	250–500	U	250–500	0.17 ± 0.02	
				>500	1.46 ± 0.07	8.4 ± 0.6	0.81 ± 0.27	>500		>500	1.46 ± 0.07	