

Item	Acceptance	Background	Fit model	Resonance parameters	Total
Fit fractions (%)					
$\rho(770)$	± 0.9	$+2.0$ -3.1	$+0.6$ -3.2	± 1.6	$+2.8$ -4.8
$\omega(782)$	± 0.08	$+0.23$ -0.06	$+0.11$ -0.10	$+0.028$ -0.014	$+0.27$ -0.14
$f_0(980)$	± 0.03	$+0.24$ -0.17	$+0.21$ -0.18	$+0.29$ -0.24	$+0.43$ -0.35
$f_2(1270)$	± 0.06	$+0.45$ -0.59	$+0.85$ -0.76	± 0.36	± 1.0
$\rho(1450)$	± 0.10	$+0.5$ -0.6	$+5.6$ -0.7	$+0.4$ -0.3	$+5.6$ -0.9
$f_0(500)$	± 0.4	$+1.6$ -0.9	$+5.7$ -1.6	± 0.6	$+6.0$ -2.0
$\lambda = 0$ fractions (%)					
$\rho(770)$	± 1.0	$+1.7$ -2.0	$+4.9$ -1.5	± 2.1	$+5.7$ -3.4
$\omega(782)$	± 1.5	$+3.5$ -1.8	$+2.8$ -3.5	$+1.2$ -1.7	$+4.9$ -4.5
$f_2(1270)$	± 0.3	± 2.4	$+3.7$ -3.4	± 1.5	± 4.5
$\rho(1450)$	± 0.9	$+4.8$ -8.4	$+5.5$ -5.1	$+4.2$ -6.1	$+8.4$ -11.6
Ratio of fit fractions (%)					
$\omega(782)/\rho(770)$	± 0.13	$+0.41$ -0.11	$+0.18$ -0.16	$+0.034$ -0.022	$+0.47$ -0.23
$f_0(980)/f_0(500)$	± 0.3	$+1.5$ -1.1	$+1.0$ -2.1	$+2.2$ -1.8	± 3.0