

Variable	Fitted value and uncertainty
$B_s^0$ mass	$5369.2^{+1.0}_{-1.0}$ MeV/ $c^2$
Signal width parameter	$13.3^{+1.0}_{-0.9}$ MeV/ $c^2$
$K_S^0 K^+ K^-$ exponential slope	$(-3.4^{+1.6}_{-1.4}) - 3$ (MeV/ $c^2$ ) $^{-1}$
$K_S^0 \pi^+ \pi^-$ exponential slope	$(-5.4^{+0.9}_{-0.8}) - 3$ (MeV/ $c^2$ ) $^{-1}$
$\alpha$	$0.74^{+0.13}_{-0.13}$
$R_{DK}$	$(4.3^{+1.0}_{-1.0}) - 2$
$R_\rho$	$(3.0^{+0.8}_{-0.8}) - 2$
$R_s$	$0.31^{+0.09}_{-0.09}$
$n(B^0 \rightarrow DK^{*0}, K_S^0 \pi^+ \pi^-)$	$84^{+15}_{-14}$
$n(B_s^0 \rightarrow D\bar{K}^{*0}, K_S^0 \pi^+ \pi^-)$	$194^{+18}_{-17}$
$n(\text{combinatorial}, K_S^0 \pi^+ \pi^-)$	$207^{+36}_{-35}$
$n(B^0 \rightarrow DK^{*0}, K_S^0 K^+ K^-)$	$6.7^{+4.8}_{-4.2}$
$n(B_s^0 \rightarrow D\bar{K}^{*0}, K_S^0 K^+ K^-)$	$36.3^{+7.1}_{-6.4}$
$n(\text{combinatorial}, K_S^0 K^+ K^-)$	$32.3^{+10.0}_{-9.0}$