

	$\frac{\mathcal{B}(B^0 \rightarrow p\bar{p}KK)}{\mathcal{B}(B^0 \rightarrow p\bar{p}K\pi)}$	$\frac{\mathcal{B}(B^0 \rightarrow p\bar{p}\pi\pi)}{\mathcal{B}(B^0 \rightarrow p\bar{p}K\pi)}$	$\frac{\mathcal{B}(B_s^0 \rightarrow p\bar{p}K\pi)}{\mathcal{B}(B^0 \rightarrow p\bar{p}K\pi)}$	$\frac{\mathcal{B}(B_s^0 \rightarrow p\bar{p}K\pi)}{\mathcal{B}(B_s^0 \rightarrow p\bar{p}KK)}$
MC statistics	3.1	2.3	4.8	4.8
Efficiency of hardware trigger	3.7	3.7	3.7	3.7
Tracking efficiency	1.1	1.1	1.1	1.1
Calibration of particle identification	1.7	1.2	1.6	1.8
Effect of B_s lifetime	-	-	2.5	0.1
Effect of charm vetoes	0.5	0.1	0.4	0.5
Shape fit components	-	-	-	-
Additional fit components	8.2	0.8	4.0	4.2
Normalisation of reflections in fit	0.2	0.1	0.7	0.8
f_d/f_s	-	-	5.8	-
Total systematic uncertainty	-	-	-	-
Statistical uncertainty	24.8	4.5	16.3	17.0